AMPLIFIER FEATURES CHART

Amplifier Output Power Rating/ Channel	Model Numbers	Amp Channels	Input Types					Signal Processing						Music Muting			Night Ringer	Remote Volume	Output Meter	Mounting			Page Number
			TEL Input* 600-ohm Balanced	MIC Inputs* Lo-Z Balanced	AUX Inputs* Hi-Z Unbalanced	Balanced Inputs Hi-Z	Modular Inputs	Audio Enhancement	Loudness Contour	ALC	EQ	Bass/Treble	Tone Control	Variable Mute	Auto Mute	Manual Mute				Wall Mount	Shelf Mount	Rack Mount	
1.5W	GA2	1			1															●	●		42
6W	GA6A	1		1	1								●								●		42
10W	C10	1	1	2 (1)	0 (1)								●		●	●				◐	●	◐	42
15W	TPU15A	1	1		1					●			●		●		◆			●			43
20W	C20	1	1	2 (1)	0 (1)								●		●	●				◐	●	◐	42
35W	C35	1	1	2 (1)	1 (2)							●			●	●					●	◐	42
35W	GS35	1	0 (1)	6 (4)	1 (2)			●	●	●	●			●	●	●		●			●	◐	41
35W	TPU35B	1	1	1	1			●		●		●		●	●	●	●			●		◐	43
35W	V35	1	●	●	●	●	8			●	●	●		●	●			●	●		●	◐	38
60W	BPA60	1			◐																●	◐	46
60W	C60	1	1	2 (1)	1 (2)							●			●	●					●	◐	42
60W	GS60	1	0 (1)	6 (4)	1 (2)			●	●	●	●			●	●	●		●			●	◐	41
60W	TPU60B	1	1	1	1			●		●		●		●	●	●	●			●		◐	43
60W	V60	1	●	●	●	●	8			●	●	●		●	●			●	●		●	◐	38
100W	C100	1	1	2 (1)	1 (2)							●			●	●					●	◐	42
100W	GS100	1	0 (1)	6 (4)	1 (2)			●	●	●	●			●	●	●		●			●	◐	41
100W/60W/20W	PM3180	3	0 (1)	2 (1)	4					●		●		●	●	●		●	●		●	◐	47
100W	TPU100B	1	1	1	1			●		●		●		●	●	●	●			●		◐	43
100W	V100	1	●	●	●	●	8			●	●	●		●	●			●	●		●	◐	38
100W	WV100	1	●	●	●	●	8			●	●	●		●	●			●	●	◐			40
125W	HTA125A	1	◐		◐																●	◐	46
150W	GS150	1	0 (1)	6 (4)	1 (2)			●	●	●	●			●	●	●		●			●	◐	41
150W	V150	1	●	●	●	●	8			●	●	●		●	●			●	●		●	◐	38
150W	WV150	1	●	●	●	●	8			●	●	●		●	●			●	●	◐			40
250W	GS250	1	0 (1)	6 (4)	1 (2)			●	●	●	●			●	●	●		●			●	◐	41
250W	HTA250A	1	◐		◐																●	◐	46
250W	TPU250	1	1	1	1			●		●		●		●	●	●	●			●		●	43
250W	V250	1	●	●	●	●	8			●	●	●		●	●			●	●		●	◐	38
250W	WV250	1	●	●	●	●	8			●	●	●		●	●			●	●	◐			40
300/600W	M300	2/1	●	●	●	2†	2			●				●	●						●	●	45
300W	X300	2	◆			2															●	●	44
450/900W	M450	2/1	●	●	●	2†	2			●				●	●						●	●	45
450W	X450	2	◆			2															●	●	44
600/1200W	M600	2/1	●	●	●	2†	2			●				●	●						●	●	45
600W	X600	2	◆			2															●	●	44

● Feature Included

● Features determined by type of module installed

◐ Balanced input available with accessory plug-in transformer (TL100 or TL600)

◐ Accessory kit required for mounting

◆ Contact closure activation only

* Some inputs are switch selectable. The number in parentheses shows the maximum number of inputs when switched.

† BAL2S balanced input module included standard; uses one modular input bay.

Specifications subject to change without notice.