

# **UHF PLL Single Channel Diversity Wireless Microphone Systems**

# Models UHF8011BP, UHF8011HH

Bogen's **UHF8011BP** and **UHF8011HH Wireless Microphone Systems** offer users the freedom to move around while speaking. System choices consist of an 1,440-channel PLL single channel UHF receiver coupled with either a body pack transmitter (UHF8011BP) with lavaliere microphone, or a wireless handheld microphone (UHF8011HH).

SYSTEM COMPONENTS

#### **UDR8011 Single Channel UHF PLL Receiver**

- Offers 1,440 user-selectable frequencies in UHF 470-490 MHz band;
  120 dB dynamic range; operation up to 500 feet line-of-sight
- Antenna diversity for maximum range and dropout protection, LCD screen, 1/4" unbalanced and XLR balanced outputs, noiseless transmitter ON/OFF switching, and digital level control for output
- Half-rack receiver design with detachable, rear dual antennas, powered by wall power adapter (included)
- Base unit: 8" W x 1-5/8" H x 6-1/2" D; 1 lb.
- Detachable Antenna: 12" Long (fully extended); 4 oz.

#### **UBP8011 Body Pack Transmitter w/Lavaliere Microphone**

- Audio mute switch allows convenient audio muting while leaving the transmitter "ON"
- LED and LCD display
- · 4-Pin, Mini-XLR connection
- Convenient, economical operation with two (2) AA alkaline or NiMH batteries (not included)
- 2-1/4" W x 4" H x 1" D; 2.8 oz. (without batteries)
- Lavaliere Mic (Sold seperately): 5 ft. long cord; 0.6 oz.

#### **UHT8011 Wireless Handheld Microphone**

- Sleek housing with internal antenna for optimum aesthetics and durable long life
- Unidirectional dynamic cartridge for optimum sound, maximum feedback rejection, and minimal handling noise
- Audio mute switch allows convenient audio muting while leaving the transmitter "ON"
- LED and LCD display
- Convenient, economical operation with two (2) AA alkaline or NiMH batteries (not included)
- 10-1/2" long x 2" dia.; 10 oz.

The UHF Reciever (UDR8011), Handheld Microphone (UHT8011), and Body Pack with Lavaliere Microphone (UBP8011) all can be purchased seperately as individual items/accessories.



### UHF8011BP

SYSTEM INCLUDES.

- UBP8011 Body-Pack with Lavaliere Mic
- · UDR8011 UHF Receiver



## **UHF8011HH**

SYSTEM INCLUDES:

- UHT8011 Handheld Mic
- UDR8011 UHF Receiver

	UDD 0044
	UDR 8011
Frequency Mode	Phase-locked loop (PLL)
Frequency Range	470 ~ 960 MHz
Sync Frequency	Ultrasonic
Bandwidth	36 MHz
Signal/Noise Ratio	> 105 dB(A)
Total Harmonic Distortion (Thd)	< 0.6% @ 1kHz
Receiving Sensitivity	-95 dBm (S/N > 80 dB)
Rejection Ratio	> 80 dB
Frequency Response	50 Hz ~ 16 kHz ± 2 dB
Antenna Type	1/2 λ BNC detachable, diversity
Antenna Power	12-15 VDC / 100mA
Display Type	LCD
Controls	Power, Set, ▲ / ▼ , Button Lock, Sync
Display Functions	Group, channel, frequency, battery level, antenna A/B, muting level, AF indication, RF indication, channel scanning, output level attenuation, volume indication
	Ref: ± 22.5 kHz Dev @ 1 kHz Tone
Audio Frequency Output Level	1/4" Jack: -10 dBV (unbalanced)
	XLRM Jack: -4 dBV (Line), -24 dBV (MIC) (balanced)
Audio Output Impedance	600Ω
Muting	Noise/Squelch muting
Output Port	1 x balanced XLRM Jack 1 x unbalanced 1/4" TS Jack
Power Supply	12-15 VDC / 300mA
Dimensions	8.35" (W) x 1.5" (H) x 5.6" (L)

The UHF Reciever (UDR8011), Handheld Microphone (UHT8011), and Body Pack
with Lavaliere Microphone (UBP8011) all can be purchased seperately as
individual items/accessories.

	UBP 8011
Frequency Mode	Phase-locked loop (PLL)
Frequency Range	470 ~ 960 MHz
Sync Frequency	Ultrasonic
RF Power Output	10m W /50 m W (as per local regulations)
RF Stability	<±10 kHz @ Fc
Modulation Frequency	± 48 kHz
Harmonic Radiation	< -50 dBc
Functions	Mute, auto off, sensitivity adjustment, input level attenuation, group, channel, frequency
Display	LCD + LED
Input	4-pin Mini XLR
Controls	Power, Mute, Set, ▲ / ▼
Battery	AA alkaline battery or NiMH rechargeable battery (x 2)
Charging	Yes
Dimensions	2.4" (W) x 3.8" (H) x 0.78" (L)

	UHT 8011
Frequency Mode	Phase-locked loop (PLL)
Frequency Range	470 ~ 960 MHz
Sync Frequency	Ultrasonic
RF Power Output	10m W / 50m W (as per local regulations)
RF Stability	< ± 10 kHz @ Fc
Modulation Frequency	± 48 kHz
Harmonic Radiation	<-50 dBc
Display	LCD + LED
Controls	Power, Mute, Set, ▲ / ▼ , Button Lock
Functions	Mute, auto off, sensitivity adjustment, group, channel, frequency
Battery	AA alkaline battery or NiMH rechargeable battery (x 2)
Charging	Yes
Dimensions	2" (W) x 10.5" (H)

#### SYSTEM ACCESSORIES









UHFUDA Unidirectional Antenna